



Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay Pipes for drains and sewers buried in ground  
DN 600 – 2.0 – FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	Pass
- Length	Pass
- Squareness of ends	Pass
- Straightness	Pass
- Continuity of invert	Pass
- Joint inter-changeability	System C
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	Pass
- Airtightness	Pass
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	Pass
- Thermal cycling stability	Pass
- Long term thermal stability	Pass
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	28 MPa
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**





Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay Plain Ended Pipes for drains and sewers buried in ground

DN 600 – 2.0 – FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	Pass
- Length	Pass
- Squareness of ends	Pass
- Straightness	Pass
- Continuity of invert	NPD
- Joint inter-changeability	R
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	Pass
- Airtightness	Pass
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	Pass
- Thermal cycling stability	Pass
- Long term thermal stability	Pass
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	28 MPa
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**





Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay connector for drains and sewers buried in ground

DN 600 – 0.75 GZ FN 57 – C

DN 600 – 0.75 GA FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	Pass
- Length	Pass
- Squareness of ends	Pass
- Angle of curvature	Pass
- Continuity of invert	Pass
- Joint inter-changeability	System C
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	Pass
- Airtightness	Pass
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	Pass
- Thermal cycling stability	Pass
- Long term thermal stability	Pass
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	NPD
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**





Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay connector for drains and sewers buried in ground  
DN 600 – 0.25 GE FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	Pass
- Length	Pass
- Squareness of ends	Pass
- Straightness	Pass
- Continuity of invert	Pass
- Joint inter-changeability	System C
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	Pass
- Airtightness	Pass
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	Pass
- Thermal cycling stability	Pass
- Long term thermal stability	Pass
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	NPD
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**





Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay connector for drains and sewers buried in ground  
DN 600 – GM FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	NPD
- Length	NPD
- Squareness of ends	NPD
- Straightness	NPD
- Continuity of invert	NPD
- Joint inter-changeability	System C
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	NPD
- Airtightness	NPD
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	NPD
- Thermal cycling stability	NPD
- Long term thermal stability	NPD
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	NPD
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**



CE

Sweillem Vitrified Clay Pipes CO.  
21

EN 295-1:2013

Vitrified Clay Junctions for drains and sewers buried in ground

DN 600-150 – 1.0 FN 57-34 – C/F 45°

DN 600-150 – 1.0 FN 57-34 – C/F 90°

DN 600-200 – 1.0 FN 57-40 – C/F 45°

DN 600-200 – 1.0 FN 57-40 – C/F 90°

DN 600-200 – 1.0 FN 57-40 – C/C 45°

DN 600-200 – 1.0 FN 57-40 – C/C 90°

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	Pass
- Length	Pass
- Squareness of ends	Pass
- Straightness	Pass
- Continuity of invert	Pass
- Joint inter-changeability	System C
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	Pass
- Airtightness	Pass
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	Pass
- Thermal cycling stability	Pass
- Long term thermal stability	Pass
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	NPD
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**





Sweillem Vitrified Clay Pipes CO.

21

EN 295-1:2013

Vitrified Clay Half Chanel for drains and sewers buried in  
ground

DN 600 – 1.0 – FN 57 - C

Reaction to fire	Class A1
Crushing strength ( $F_N$ )	57 KN/m
<b>Longitudinal bending strength:</b>	
- Bending moment resistance (BMR)	NPD
<b>Dimensional tolerances, concerning:</b>	
- Internal diameter	NPD
- Length	Pass
- Squareness of ends	Pass
- Straightness	NPD
- Continuity of invert	NPD
- Joint inter-changeability	NPD
<b>Watertightness (gas and liquid) and permeability as:</b>	
- Watertightness	NPD
- Airtightness	NPD
<b>Durability of watertightness against:</b>	
- Chemical and physical resistance to effluent	NPD
- Thermal cycling stability	NPD
- Long term thermal stability	NPD
<b>Durability of crushing strength and longitudinal bending strength, against:</b>	
- Chemical resistance	< 0.15
- Resistance against high pressure water jetting	NPD
- Water absorption	< 6.0 % Wt.

**HEAD OF QUALITY CONTROL**  
**Ahmed Mohamed Wahid**

